# ZK1090-3133-6xxx | EtherCAT cable, PUR, 1 x 4 x AWG22, capable of torsion

## M8, plug, straight, male, 4-pin, A-coded – M8, plug, angled, male, 4-pin, A-coded



## Plugs

| Electrical data | Head A | Head B |
|---|---|---|
| Rated voltage | 50 V AC/60 V DC (according to IEC 61076-2-104) | 50 V AC/60 V DC (according to IEC 61076-2-104) |
| Rated current | 4 A at 40°C (according to IEC 61076-2-104) | 4 A at 40°C (according to IEC 61076-2-104) |
| Shielding | yes | yes |
| Insulation resistance | ≥ 100 GΩ (according to IEC 60512) | ≥ 100 GΩ (according to IEC 60512) |
| **Mechanical data** | | |
| Installation size | M8 | M8 |
| Connector type | plug | plug |
| Configuration | straight | angled |
| Contact type | male | male |
| Number of positions (face) | 4-pin | 4-pin |
| Coding | A-coded | A-coded |
| Recommended torque, nut | 0.4 Nm | 0.4 Nm |

| | | |
|---|---|---|
| Mating cycles | ≥ 100 | ≥ 100 |
| Way of locking | screw | screw |
| Weight | 0.028 kg (0.0617 lb) | 0.028 kg (0.0617 lb) |
| Body color | black | black |
| Body material | TPU, UL94 | TPU, UL94 |
| Coupling nut material | GD-Zn, Ni | GD-Zn, Ni |
| Seal | FPM | FPM |
| Contact carrier color | green | green |
| Contact carrier material | PA 6, UL 94 V0 | PA, UL 94 |
| Contact plating | Ni, Au gal. | Ni, Au gal. |
| Contact material | CuZn | CuZn |
| **Environmental data** | | |
| Special features | halogen-free, flame-resistant as per IEC 60332-1-2, oil-resistant as per DIN EN 60811-2-1 | halogen-free, flame-resistant as per IEC 60332-1-2, oil-resistant as per DIN EN 60811-2-1 |
| RoHS compliant | yes | yes |
| Ambient temperature (operation) | -30...+70°C, -22...+158°F | -30...+70°C, -22...+158°F |
| Protection rating | IP65/67 in screwed condition (according to IEC 60529) | IP65/67 in screwed condition (according to IEC 60529) |
| Pollution level | 3/2 (according to IEC 60664-1) | 3/2 (according to IEC 60664-1) |

## Cable

| | |
|---|---|
| **Electrical data** | |
| Rated voltage | 600 V |
| Insulation resistance | ≥ 5GΩ * km |
| Mutual capacitance | 48 nF/km |
| Characteristic impedance (Ethernet) | 100 Ω ±15 Ω |
| Loop resistance (Ethernet) | ≤ 115 Ω/km |
| Signal running time (Ethernet) | 5.3 ns/m |
| Electrical parameters (Ethernet) | based on Cat.5 |
| Test voltage | 1500 V, 50 Hz, 1 min. |
| **Mechanical data** | |
| Cable structure (Ethernet) | star quad |
| Conductor construction (Ethernet) | 19-strand |
| Cross-section (Ethernet) | 1 x 4 x 0.34 mm² (AWG22) |
| Outer cable diameter | 6.6 mm ± 0.2mm (0.259" ± 0.0079") |
| Min. bending radius, moved | 10 x outer cable diameter |

| | |
|---|---|
| Min. bending radius, fixed installation | 5 x outer cable diameter |
| Conductor material (Ethernet) | tinned copper |
| Shielding | two layers of conductive wrapping and braiding of special wires |
| Optical covering factor of shielding (Ethernet) | ≥ 85 % |
| Use | suitable for torsion/robotic applications |
| Max. acceleration | 20 m/s² |
| Max. speed | 4 m/s |
| Max. travel distance | 5 m |
| Max. number of cycles | 1 million |
| Jacket color | green |
| Material jacket | PUR (polyurethane) |
| Material jacket, further characteristics of | halogen-free, flame-retardant, matt and low adhesion |
| Wire color code | yellow, orange, white, blue |
| Wire insulation material | PO (Polyolefine) |
| Printing on the jacket | XXXX Beckhoff Automation GmbH & Co. KG-Germany-ZB9021 EtherCAT Cat5e Torsion AWG22/19 E170315 cRUus> AWM21209 AWM I/II A/B 90°C 600V MM/YY CE |
| Printing color | black |
| Torsion angle in °/m | max. ± 180°/m |
| Torsion speed | 36 cycle/min. |
| Number of torsion cycles | 5 million |
| Load weight | 20 N |
| Claimed torsion length | 1 m |

| **Environmental data** | |
|---|---|
| Operation temperature range, moved | -30...+90°C, -22...+194°F |
| Operation temperature range, fixed installation | -40...+90°C, -40...+194°F |
| Oil resistance | according to DIN EN 60811-404 (7x24 h/90 °C) |
| Flame-retardant | VW-1 Flame Test UL 1581 section 1080 and IEC 60332-1-2 |
| Halogen-free | according to IEC 60754 or DIN VDE 0472 part 815 |
| UL | yes, UL E-file number: E170315 |

**Attenuation**


Max. insertion loss

| Frequency [MHz] | **1** | **4** | **10** | **16** | **20** | **31.25** | **62.5** | **100** |
|---|---|---|---|---|---|---|---|---|
| [db/100 m] | - | 4.9 | 7.8 | 9.9 | 11.1 | 14.1 | 62.5 | 26.4 |
| [db/100 ft] | - | 1.5 | 2.4 | 3 | 3.4 | 4.3 | 19.1 | 8 |


Min. near-end crosstalk attenuation

| Frequency [MHz] | 1 | 4 | 10 | 16 | 20 | 31.25 | 62.5 | 100 |
|---|---|---|---|---|---|---|---|---|
| [db/100 m] | - | 56.3 | 50.3 | 47.2 | 45.8 | 42.9 | 38.4 | 35.3 |
| [db/100 ft] | - | 17.2 | 15.3 | 14.4 | 14 | 13.1 | 11.7 | 10.8 |

## Pin assignment




## Dimensions




| | |
|---|---|
| A1 | 41.00 mm |
| A2 | Ø 10.1 mm |
| B1 | 29.80 mm |
| B2 | 26.30 mm |

# Notes

- Depending on the cable length (L), the following length tolerances apply:
  0 m...<0.2 m: ± 10 mm | 0.2...4.0 m: + 40 mm | ≥ 4.0 m: + 1%
- Illustrations similar
- Further cable length on request.

## CE, UL

| | |
|---|---|
| CE | yes |
| UL | yes, UL E-file number: E499669 |

| Ordering information | Length |
|---|---|

| | |
|---|---|
| ZK1090-3133-6010 | 1.00 m |
| ZK1090-3133-6040 | 4.00 m |

Further length on request

| Accessories | |
|---|---|
| ZB8801-0000 | torque wrench for hexagonal plugs, adjustable |
| ZB8801-0001 | torque cable key, M8/wrench size 9, for ZB8801-0000 |
| ZB8803-0001 | Flange/Panel feed-through for M8 pre-assembled, for fixing the connector, plastic, including screws, washers and lock nuts |



Products marked with a crossed-out wheeled bin shall not be discarded with the normal waste stream. The device is considered as waste electrical and electronic equipment. The national regulations for the disposal of waste electrical and electronic equipment must be observed.

Beckhoff®, ATRO®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, MX-System®, Safety over EtherCAT®, TC/BSD®, TwinCAT®, TwinCAT/BSD®, TwinSAFE®, XFC®, XPlanar® and XTS® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 03/2026

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressively agreed in the terms of contract.