



ZK1096-9191-3xxx | Industrial Ethernet/EtherCAT G/G10 patch cable, Cat.6A, PVC, 4 x 2 x AWG26, fixed installation



RJ45, plug, straight, male, 8-pin – RJ45, plug, straight, male, 8-pin



Plugs



Electrical data	Head A	Head B
Rated voltage	160 V	160 V
Rated current	1 A at 50°C	1 A at 50°C
Shielding	yes	yes
Insulation resistance	$\geq 500 \text{ M}\Omega$	$\geq 500 \text{ M}\Omega$
Mechanical data		
Installation size	RJ45	RJ45
Connector type	plug	plug
Configuration	straight	straight
Contact type	male	male
Number of positions (face)	8-pin	8-pin
Mating cycles	≥ 750	≥ 750
Body color	black	black
Body material	PVC UL94 HB	PVC UL94 HB

Contact carrier color	transparent	transparent
Contact carrier material	PC UL 94 V-0	PC UL 94 V-0
Contact plating	Au over Ni	Au over Ni
Contact material	phosphorus bronze	phosphorus bronze
Environmental data		
Special features	10 GBit Ethernet acc. to IEEE802-3an Category 6A/Klasse EA acc. to EN 50173-1 Category 6A acc. to ANSI/TIA/EIA-568-C.2	10 GBit Ethernet acc. to IEEE802-3an Category 6A/Klasse EA acc. to EN 50173-1 Category 6A acc. to ANSI/TIA/EIA-568-C.2
Shock resistance	250 m/s ²	250 m/s ²
Vibration resistance	50 m/s ²	50 m/s ²
RoHS compliant	yes	yes
Ambient temperature (operation)	-40...+70°C, -40...+158°F	-40...+70°C, -40...+158°F
Protection rating	IP20	IP20
Approvals	UL	UL

Cable

Electrical data	
Rated voltage	125 V
Insulation resistance	≥ 150 MΩ * km
Unbalanced capacitance to ground	1600 pF/km
Mutual capacitance	46 pF/m at 1 kHz
Characteristic impedance	100 Ω ± 15 Ω (100 MHz)
Loop resistance	≤ 290 Ω/km
Unbalanced resistance (Ethernet)	≤ 2 % in the pair, ≤ 4 % between the pairs
Dielectric strength wire/wire	750 V
Dielectric strength wire/shield	750 V
Signal running time (Ethernet)	4.27 ns/m
Electrical parameters (Ethernet)	Cat.7 acc. to EN50288-4-2
Test voltage	750 V, 50 Hz, 1 min.
Mechanical data	
Cable structure	S/FTP
Cable structure (Ethernet)	twisted shielded pair
Conductor construction (Ethernet)	7-strand
Cross-section (Ethernet)	4 x 2 x 0.14 mm ² (AWG26)
Outer cable diameter	6.2 mm ± 0.2mm (0.244" ± 0.0079")
Min. bending radius, moved	8 x outer cable diameter
Min. bending radius, fixed installation	4 x outer cable diameter

Weight	41 kg/km (27.55 lb/1000 ft)
Conductor material (Ethernet)	bare copper
Shielding	braiding of tinned copper wires, metallized plastic fleece for pair shielding
Optical covering factor of shielding (total)	≥ 60 %
Use	fixed installation
Jacket color	green
Material jacket	PVC (polyvinyl chloride)
Wire color code	white/orange, orange, white/green, green, blue, white/blue, white/brown, brown
Wire insulation material	PE (polyethylene)
Printing on the jacket	Cat.7 S/FTP 4x2xAWG26/7 PVC PIMF RU AWM STYLE 20276 E81280 IEC 60332-1 "production batch no." "length in meters" CE
Printing color	blue
Environmental data	
Operation temperature range, fixed installation	-20...+75°C, -4...+167°F
Ambient temperature, transport/storage	-10...+60°C, -14...+140°F
Acid, lye and solvent resistance	depends on medium, concentration, temperature and duration
Special features	Series of ISO/IEC 11801-x; Class F, Series of EN 50173-x; Class F, IEEE802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T, IEEE 802.3: Power over Ethernet PoE; PoE+
Flame-retardant	according to IEC 60332-1
UL	yes, UL E-file number: E81280

Pin assignment**Dimensions**

A1	42.00 mm
B1	42.00 mm

Notes

- Depending on the cable length (L), the following length tolerances apply:
0 m...<0.2 m: ± 10 mm | 0.2...4.0 m: + 40 mm | ≥ 4.0 m: + 1%
- Illustrations similar
- Further cable length on request.

CE, UL	
CE	yes

Ordering information	Length
ZK1096-9191-3001	0.17 m
ZK1096-9191-3002	0.26 m
ZK1096-9191-3003	0.30 m
ZK1096-9191-3005	0.50 m
ZK1096-9191-3010	1.00 m
ZK1096-9191-3015	1.50 m
ZK1096-9191-3020	2.00 m
ZK1096-9191-3030	3.00 m
ZK1096-9191-3040	4.00 m
ZK1096-9191-3050	5.00 m
ZK1096-9191-3060	6.00 m
ZK1096-9191-3080	8.00 m
ZK1096-9191-3100	10.00 m
ZK1096-9191-3120	12.00 m
ZK1096-9191-3150	15.00 m
ZK1096-9191-3200	20.00 m
ZK1096-9191-3250	25.00 m
ZK1096-9191-3300	30.00 m
ZK1096-9191-3350	35.00 m
ZK1096-9191-3400	40.00 m
ZK1096-9191-3450	45.00 m
ZK1096-9191-3500	50.00 m
ZK1096-9191-3850	85.00 m

Further length on request

Accessories

ZK1096-9696-0000

RJ45, socket, straight, female, 8-pin – RJ45, socket, straight, female, 8-pin



Products marked with a crossed-out wheeled bin shall not be discarded with the normal waste stream. The device is considered as waste electrical and electronic equipment. The national regulations for the disposal of waste electrical and electronic equipment must be observed.

Beckhoff®, ATRO®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, MX-System®, Safety over EtherCAT®, TC/BSD®, TwinCAT®, TwinCAT/BSD®, TwinSAFE®, XFC®, XPlanar® and XTS® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2026

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.