

ZK2000-2364-0xxx | Sensor cable, PUR, 3 x 0.25 mm², drag-chain suitable



M8, plug, angled, male, 3-pin, A-coded – M12, socket, angled, female, 4-pin, A-coded



Plugs



Electrical data	Head A	Head B
Rated voltage	50 V AC/60 V DC (according to IEC 61076-2-104)	250 V (according to IEC 61076-2-101)
Rated current	4 A at 40°C (leaning on IEC 61076-2-104)	4 A at 40°C (according to IEC 61076-2-101)
Rated current (signal/24V)	4 A at 40°C (acc.to IEC 61076-2-104)	-
Rated impulse voltage	-	1.5 kV
Shielding	no	no
Contact resistance	-	< 10 mΩ
Insulation resistance	≥ 10 GΩ (according to IEC 60512-2)	≥ 100 MΩ (according to IEC 60512)
Mechanical data		
Installation size	M8	M12
Connector type	plug	socket
Configuration	angled	angled
Contact type	male	female

Number of positions (face)	3-pin	4-pin
Coding	A-coded	A-coded
Recommended torque, nut	0.4 Nm	0.6 Nm
Mating cycles	≥ 100 (according to IEC 60512-9a)	≥ 100 (according to IEC 60512-9a)
Way of locking	screw	screw
Weight	0.028 kg (0.0617 lb)	0.023 kg (0.0507 lb)
Body color	black	black
Body material	TPU, UL94	PA6 GF, UL 94 HB
Coupling nut material	CuZn, Ni	CuZn, Ni
Seal	FPM	elastomers
O-ring	-	FPM/NBR
Contact carrier color	red	red
Contact carrier material	TPU GF, UL 94	PA 6, UL 94 V0
Contact plating	Ni, Au gal.	Au
Contact material	CuZn	CuZn, Ni b/Au 0.2 gal.
Environmental data		
Special features	halogen-free, flame-resistant as per IEC 60332-1-2, oil-resistant as per DIN EN 60811-2-1	-
RoHS compliant	yes	yes
Ambient temperature (operation)	-30...+80°C, -22...+176°F	-30...+85°C, -22...+185°F
Protection rating	IP67 in screwed condition (according to IEC 60529)	IP65/67 in screwed condition (according to IEC 60529)
Pollution level	3/2 (according to IEC 60664-1)	3/2 (according to IEC 60664-1)

Cable

Electrical data	
Rated voltage	≤ 300 V
Insulation resistance	≥ 10 GΩ (according to IEC 60512-2)
Wire resistance (signal/24V)	≤ 58.0 Ω/km (20°C)
Test voltage	≥ 3000 V
Mechanical data	
Conductor construction (signal/24V)	32 x 0.10 mm
Cross-section	3 x 0.25 mm ² (AWG24)
Outer cable diameter	4.4 mm ± 0.15 mm (0.173" ± 0.0059")
Min. bending radius, moved	6 x outer cable diameter
Weight	28 kg/km (18.8 lb/1000 ft)

Shielding	no
Use	drag-chain suitable
Max. acceleration	10 m/s ²
Max. speed	5 m/s
Max. number of cycles	10 million at max. 20 m travel distance, 2 million at max. 100 m travel distance
Jacket color	black
Material jacket	PUR (polyurethane)
Wire color code	brown, blue, black
Wire insulation material	PP (polypropylene)
Printing on the jacket	Li9Y11Y 3x0.25mm ² E257058 CRUus (UL-Logo) AWM Style 20549 AWM II A/B 80°C 300 V FT2
Printing color	white
Environmental data	
Operation temperature range, moved	-25...+80°C, -13...+176°F
Oil resistance	Oil and greases resistant
Flame-retardant	according to cULus 20549
Halogen-free	according to DIN VDE 0472 part 815
CE	yes
UL	yes, UL E-file number: E257058

Pin assignment**Dimensions**

A1	27.50 mm
----	----------

A2	26.30 mm
B1	35.00 mm
B2	26.80 mm

Notes

- Depending on the cable length (L), the following length tolerances apply:
0 m...<0.2 m: ± 10 mm | 0.2...4.0 m: $+ 40$ mm | ≥ 4.0 m: $+ 1\%$
- Illustrations similar
- Further cable length on request.

CE, UL	
CE	yes

Ordering information	Length
ZK2000-2364-0005	0.50 m
ZK2000-2364-0010	1.00 m
ZK2000-2364-0015	1.50 m
ZK2000-2364-0020	2.00 m
ZK2000-2364-0050	5.00 m

Further length on request

Accessories	
ZB8801-0000	torque wrench for hexagonal plugs, adjustable
ZB8801-0001	torque cable key, M8/wrench size 9, for ZB8801-0000
ZB8801-0002	torque cable key, M12/wrench size 13, for ZB8801-0000



Products marked with a crossed-out wheeled bin shall not be discarded with the normal waste stream. The device is considered as waste electrical and electronic equipment. The national regulations for the disposal of waste electrical and electronic equipment must be observed.

Beckhoff®, ATRO®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, MX-System®, Safety over EtherCAT®, TC/BSD®, TwinCAT®, TwinCAT/BSD®, TwinSAFE®, XFC®, XPlanar® and XTS® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 03/2026

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.