ZK2020-3334-3xxx | Power cable, PVC, 4 x 0.34 mm², fixed installation

M8, plug, angled, male, 4-pin, A-coded – M8, socket, angled, female, 4-pin, A-coded



Plugs

Electrical data	Head A	Head B
Rated voltage	50 V AC/60 V DC (according to IEC 61076-2-104)	50 V AC/60 V DC (according to IEC 61076-2-104)
Rated current	4 A at 40°C (leaning on IEC 61076-2-104)	4 A at 40°C (leaning on IEC 61076-2-104)
Shielding	no	no
Contact resistance	< 5 mΩ	-
Insulation resistance	≥ 10 GΩ (according to IEC 60512-2)	≥ 10 GΩ (according to IEC 60512-2)
Mechanical data		
Installation size	M8	M8
Connector type	plug	socket
Configuration	angled	angled
Contact type	male	female
Number of positions (face)	4-pin	4-pin
Coding	A-coded	A-coded

Recommended torque, nut	0.4 Nm	0.4 Nm
Mating cycles	≥ 100 (according to IEC 60512-9a)	≥ 100 (according to IEC 60512-9a)
Way of locking	screw	screw
Weight	0.028 kg (0.0617 lb)	0.028 kg (0.0617 lb)
Body color	black	black
Body material	TPU, UL94	TPU, UL94
Coupling nut material	CuZn, Ni	CuZn, Ni
Seal	FPM	FPM
Contact carrier color	red	red
Contact carrier material	TPU GF, UL 94	TPU GF, UL 94
Contact plating	Ni, Au gal.	Ni, Au gal.
Contact material	CuZn	CuZn
Environmental data		
Special features	halogen-free, flame-resistant as per IEC 60332-1-2, oil-resistant as per DIN EN 60811-2-1	halogen-free, flame-resistant as per IEC 60332-1-2, oil-resistant as per DIN EN 60811-2-1
RoHS compliant	yes	yes
Ambient temperature (operation)	-30...+80°C, -22...+176°F	-30...+80°C, -22...+176°F
Protection rating	IP65/67 in screwed condition (according to IEC 60529)	IP65/67 in screwed condition (according to IEC 60529)
Pollution level	3/2 (according to IEC 60664-1)	3/2 (according to IEC 60664-1)

Cable


Electrical data	
Rated voltage	≤ 300 V
Insulation resistance	≥ 10 GΩ (according to IEC 60512-2)
Wire resistance (power)	≤ 58.0 Ω/km
Test voltage	≥ 3000 V
Mechanical data	
Conductor construction (power)	42 x 0.10 mm
Cross-section	4 x 0.34 mm² (AWG22)
Outer cable diameter	4.7 mm ± 0.15 mm (0.185" ± 0.0059")
Min. bending radius, fixed installation	10 x outer cable diameter
Weight	31 kg/km (20.8 lb/1000 ft)
Shielding	no
Use	fixed installation
Wall thickness of wire insulation (power)	≥ 0.21 mm

Jacket color	gray
Material jacket	PVC (polyvinyl chloride)
Wire color code	white, blue, black, brown
Wire insulation material	PVC (polyvinyl chloride)
Printing color	white


Environmental data

Operation temperature range, fixed installation	-25...+80°C, -13...+176°F
Flame-retardant	according to DIN EN 60332-2-2
Halogen-free	no

Pin assignment



Dimensions



A1	27.50 mm
A2	26.30 mm
B1	27.50 mm
B2	19.20 mm

Notes

- Depending on the cable length (L), the following length tolerances apply:
  0 m...<0.2 m: ± 10 mm | 0.2...4.0 m: + 40 mm | ≥ 4.0 m: + 1%
- Illustrations similar
- Further cable length on request.

CE, UL

CE	yes
UL	yes, UL E-file number: E480185

Ordering information	Length
ZK2020-3334-3005	0.50 m
ZK2020-3334-3035	3.50 m

Further length on request

Accessories	
ZB8801-0000	torque wrench for hexagonal plugs, adjustable
ZB8801-0001	torque cable key, M8/wrench size 9, for ZB8801-0000



Products marked with a crossed-out wheeled bin shall not be discarded with the normal waste stream. The device is considered as waste electrical and electronic equipment. The national regulations for the disposal of waste electrical and electronic equipment must be observed.

Beckhoff®, ATRO®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, MX-System®, Safety over EtherCAT®, TC/BSD®, TwinCAT®, TwinCAT/BSD®, TwinSAFE®, XFC®, XPlanar® and XTS® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 03/2026

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressively agreed in the terms of contract.