


ZK4500-8004-xxxx | Motor connection cable 2.5 mm² with M23 speedtec[®] plug, fixed installation



M23, plug, straight, female, Power: 3+PE, Signal: 5 – Pitch dimension 7.62 mm, plug, angled, female, 4-pin – Pitch dimension 3.50 mm, plug, straight, female, 5-pin



Plugs

Electrical data	Head A	Head B	Head D
Rated voltage (power)	630 V AC/DC	1000 V AC/DC (according to IEC 60664-1, IEC 61984), 600 V (according to UL 1059)	-
Rated voltage (signal/24V)	250 V AC/DC	-	320 V (according to IEC 60664-1, IEC 61984), 300 V (according to UL 1059)
Rated current (power)	30 A max.	41 A at 40°C (according to IEC 60664-1, IEC 61984), 40.5 A at 40°C (according to UL 1059)	-
Rated current (signal/24V)	7 A max.	-	10 A at 40°C (according to IEC 60664-1, IEC 61984), 10 A at 40°C (according to UL 1059)
Rated impulse voltage (power)	6.0 kV	8.0 kV	-

Rated impulse voltage (signal/24V)	2.5 kV	-	2.5 kV
Contact resistance	< 5 mΩ (signal), < 3 mΩ (power)	4.5 mΩ	< 5 mΩ
Insulation resistance	-	≥ 100 MΩ (according to IEC 60512)	≥ 100 MΩ (according to IEC 60512)
Insulation group	-	II	IIIa
Mechanical data			
Accessories type	Connectors	Connectors	Connectors
Installation size	M23	Pitch dimension 7.62 mm	Pitch dimension 3.50 mm
Connector type	plug	plug	plug
Configuration	straight	angled	straight
Contact type	female	female	female
Number of positions (face)	Power: 3+PE, Signal: 5	4-pin	5-pin
Wire termination	crimp connection	Clamping yoke connection	Clamping yoke connection
Recommended torque, screw termination	-	0.5...0.6 Nm	0.2...0.25 Nm
Recommended torque, screw flange	-	0.6 Nm	0.15...0.2 Nm
Mating cycles	500	25	25
Way of locking	Speedtec®	screw	screw
Weight	0.143 kg (0.3153 lb)	0.052 kg (0.1146 lb)	0.004 kg (0.0088 lb)
Body color	metal	black, similar to RAL 9011	black, similar to RAL 9011
Body material	zinc diecast/nickel plated	PA GF, UL 94 V-0	PBT, UL 94 V-0
Seal	FKM	-	-
Clamp ring	brass/nickel plated	-	-
Contact carrier material	PA 6.6 mod., UL 94 V-0	PA GF, UL 94 V-0	PBT, UL 94 V-0
Contact material	brass/gold plated	copper alloy	copper alloy
Max. wire cross-section	-	AWG24...AWG8 (0.2 mm²... 10 mm²)	AWG28...AWG14 (0.2 mm²... 1.5 mm²)
Environmental data			
Special features	Max. height for operation 2000 m	-	-
Ambient temperature (operation)	-20...+130°C, -4...+266°F	-50...+125°C, -58...+257°F	-50...+100°C, -58...+212°F
Protection rating	IP66/67 in screwed condition	IP20	IP20
Pollution level	3 (according to VDE 0110/EN61984 part 6.19.2.2)	3	3
UL	yes, UL E-file number: E247738	yes, UL E-file number: E60693	yes, UL E-file number: E60693


Overvoltage category	3 (according to VDE 0110/EN61984 part 6.19.2.2)	3	3
----------------------	---	---	---

Cable


Electrical data	
Operating voltage	max. 1000 V AC (UL)
Insulation resistance	$\geq 500 \text{ M}\Omega \cdot \text{km}$ (DIN EN 50395)
Mutual capacitance	Signal: $45 \pm 15 \text{ pF/m}$, Power: 90 pF/m (at 800 Hz according to EN 50289-1-5)
Wire resistance (power)	$\leq 7.98 \text{ }\Omega/\text{km}$ (DIN EN 50395)
Wire resistance (signal/24V)	$\leq 55.0 \text{ }\Omega/\text{km}$ (DIN EN 50395)
Wire resistance (brake)	$\leq 19.5 \text{ }\Omega/\text{km}$ (DIN EN 50395)
Characteristic impedance	Signal: $110 \text{ }\Omega \pm 10 \text{ }\Omega$ (10 MHz) acc. to EN50289-1-11
Dielectric strength wire/wire (power)	4 kV 50 Hz 5 min. (DIN VDE 0472 T.509C)
Dielectric strength wire/shield (power)	4 kV 50 Hz 5 min. (DIN VDE 0472 T.509C)
Dielectric strength wire/wire (signal/24V)	3 kV 50 Hz 1 min. (DIN VDE 0472 T.509C)
Dielectric strength wire/shield (signal/24V)	3 kV 50 Hz 1 min. (DIN VDE 0472 T.509C)
Mechanical data	
Cross-section (power)	2.50 mm^2 (approx. AWG14)
Cross-section (signal)	AWG22 (approx. 0.34 mm^2)
Cross-section (brake)	1.00 mm^2 (approx. AWG18)
Outer cable diameter	$13.8 \text{ mm} \pm 0.4 \text{ mm}$ ($0.5433'' \pm 0.0157''$)
Min. bending radius, fixed installation	5 x outer cable diameter
Conductor material	copper bare
Optical covering factor of shielding	$\geq 85\%$
Use	fixed installation
Jacket color	orange
Material jacket	PVC (polyvinyl chloride)
Wire insulation material	PP (polypropylene)
Printing color	black
Torsion angle in $^\circ/\text{m}$	max. $\pm 30^\circ/\text{m}$
Max. tensile load, dynamic	20 N/mm^2
Max. tensile load, static	50 N/mm^2
Environmental data	
Operation temperature range, fixed installation	$-20...+80^\circ\text{C}$, $-4...+176^\circ\text{F}$

Oil resistance	according to DIN EN 60811-2-1, HD22.10 appendix A
Flame-retardant	according to IEC 60332-1-2 UL758 cable flame test
Halogen-free	no
Silicone-free	yes
RoHS compliant	yes
Approvals	UL758 (AWM) Style 2570 (jacket) and Style 10492 (core)

Pin assignment



Dimensions



A1	79.00 mm
A2	28.00 mm
B1	45.00 mm
B2	45.00 mm
D1	19.00 mm
D2	25.00 mm

Notes

- Depending on the cable length (L), the following length tolerances apply: $\pm 2\text{-}3\%$

- Illustrations similar
- The last three digits of the ordering information is the cable length in decimeters, e.g. ZK4xxx-xxxx-x020 = cable length 2.00 m

Ordering information	Length
ZK4500-8004-0010	1.00 m
ZK4500-8004-0015	1.50 m
ZK4500-8004-0020	2.00 m
ZK4500-8004-0030	3.00 m
ZK4500-8004-0040	4.00 m
ZK4500-8004-0050	5.00 m
ZK4500-8004-0060	6.00 m
ZK4500-8004-0070	7.00 m
ZK4500-8004-0080	8.00 m
ZK4500-8004-0090	9.00 m
ZK4500-8004-0100	10.00 m
ZK4500-8004-0110	11.00 m
ZK4500-8004-0120	12.00 m
ZK4500-8004-0130	13.00 m
ZK4500-8004-0140	14.00 m
ZK4500-8004-0150	15.00 m
ZK4500-8004-0160	16.00 m
ZK4500-8004-0170	17.00 m
ZK4500-8004-0180	18.00 m
ZK4500-8004-0190	19.00 m
ZK4500-8004-0200	20.00 m
ZK4500-8004-0210	21.00 m
ZK4500-8004-0220	22.00 m
ZK4500-8004-0230	23.00 m
ZK4500-8004-0240	24.00 m
ZK4500-8004-0250	25.00 m
ZK4500-8004-0270	27.00 m
ZK4500-8004-0280	28.00 m
ZK4500-8004-0290	29.00 m
ZK4500-8004-0300	30.00 m
ZK4500-8004-0310	31.00 m
ZK4500-8004-0320	32.00 m
ZK4500-8004-0330	33.00 m

ZK4500-8004-0350	35.00 m
ZK4500-8004-0370	37.00 m
ZK4500-8004-0400	40.00 m
ZK4500-8004-0420	42.00 m
ZK4500-8004-0450	45.00 m
ZK4500-8004-0500	50.00 m
ZK4500-8004-0530	53.00 m
ZK4500-8004-0550	55.00 m
ZK4500-8004-0600	60.00 m
ZK4500-8004-0700	70.00 m
ZK4500-8004-0800	80.00 m

Beckhoff®, ATRO®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, MX-System®, Safety over EtherCAT®, TC/BSD®, TwinCAT®, TwinCAT/BSD®, TwinSAFE®, XFC®, XPlanar® and XTS® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2026

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.