


ZS2020-6741 | M12, power, field assembly, socket, angled, female, 5-pin, L-coded, IP67




M12, socket, angled, female, 5-pin, L-coded



Electrical data	
Rated voltage	630 V AC/DC (according to IEC 61076-2-111)
Rated current	16 A at 40°C with 2.5 mm ² wires (according to IEC 61076-2-111)
Contact resistance	< 10 mΩ
Insulation resistance	≥ 100 MΩ
Mechanical data	
Accessories type	Connectors
Installation size	M12
Connector type	socket
Configuration	angled
Contact type	female
Number of positions (face)	5-pin
Coding	L-coded
Wire termination	screw connection
Recommended torque, nut	0.6 Nm
Recommended torque, screw termination	0.2 Nm

Mating cycles	≥ 100
Body color	black
Flange housing material	PA 66 UL 94 HB
Coupling nut material	PA
Contact material	brass/gold plated
Max. wire cross-section	AWG18...AWG12 (0.75 mm ² ...2.50 mm ²)
Stripping length	4...5 mm
Max. cable outer diameter	8.0...12 mm
Environmental data	
Special features	It is possible to turn and fix the contact carrier in 4 different 90° positions
RoHS compliant	yes
Ambient temperature (operation)	-25...+85°C, -13...+185°F
Protection rating	IP67
UL	yes, UL2238
Application Note	Robust and high power transmission up to 16 A and 63 V for DC applications

Dimensions

A1	~60 mm
A2	Ø 24 mm
A3	AF22

Notes

- Illustrations similar

Ordering information	
ZS2020-6741	M12, socket, field assembly, angled, female, 5-pin, L-coded, 0.5...2.5 mm ² , Ø 8...12 mm

Accessories	
ZB8801-0000	torque wrench for hexagonal plugs, adjustable
ZB8801-0004	Torque cable key, M12 (field assembly Power)wrench size 22, for ZB8801-0000

Beckhoff®, ATRO®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, MX-System®, Safety over EtherCAT®, TC/BSD®, TwinCAT®, TwinCAT/BSD®, TwinSAFE®, XFC®, XPlanar® and XTS® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2026

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.