Honeywell | Sensing and Control

Search the entire website and product database

Start Here ... Search

HOME | ABOUT US | KEY INDUSTRIES SERVED | PRODUCTS & INFORMATION | NEWS & EVENTS | SALES & SUPPORT | LOGIN

LSA1A-1A

(Home : Products : Switches : MICRO SWITCH™ Limit Switches : MICRO SWITCH™ Heavy-Duty Limit Switches : HDLS)



Actual product appearance may vary.

Series HDLS Plug-in: Side Rotary; 1NC 1NO SPDT Snap Action; 0.5 in - 14NPT conduit

click here to download Hi-Res image

Sales & Service | Distributor Inventory

Specs

Product Specifications

Availability	Global
Operating Force (OF)	0,45 N m [4 in lb] max.
Pretravel (PT)	15° max.
Overtravel (OT)	60° min.
Differential Travel (DT)	5° max.
Product Type	MICRO SWITCH™ Heavy-Duty Limit Switches
Actuator	Side Rotary
Lever Type	1.5 in Fixed Length Lever with front mounted Nylon Roller (.75 in dia. x .25 in wide)
Circuitry	1NC 1NO SPDT Snap Action, Double Break
Ampere Rating	10 A (Thermal)
Supply Voltage	600 Vac and 250 Vdc max.
Housing Material	Zinc Die-Cast
Termination Type	0.5 in - 14NPT Conduit
Housing Type	HDLS Plug-in
Series Name	HDLS
Sealing	NEMA 1, 3, 4, 4X, 6, 6P, 12, 13
UL File #	E37138
Operating Temperature	-12 °C to 121 °C [10 °F to 250 °F]
Comment	Lever Included
Agency Approvals and Standards	UL, CE, CSA, CCC. EN60947-1, EN60947-5-1
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Industrial

Distributor Inventory

Input part number for stock availability

Narrow Your Search

Modify Your Search

Products

Select Option

Technology

Select Option

Industries Served

Select Option

Product Type: All Product Types

Industry: All Industries

Search Term: Start Here ...

New Products Only

Entire Product Catalog

Search

eCOM Login
Request Access to eCOM
Rep/AD Portal Login
Rep/AD Portal Access Request
Sample Request
Digital University Login
Limitless Microsite
Supplier Microsite

Application Demos
White Papers
Application Notes
Literature Request
Data Sheets
Videos

Customer Service
Technical Support
Global Sales & Service
Website Feedback