Product specifications

Eaton DILM32-10(24V60HZ)

Catalog Number: DILM32-10(24V60HZ)

Eaton XT IEC large contactor, 32A,24 Vac, 60 Hz, 1NO, 32A, Frame C, 45 mm, 60 Hz, 2, 5/ 10, 10, 20, 25 (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Screw terminals, Full voltage non-reversing miniature contactor, 15 kW



Photo is representative

General specifications

Product Name
Eaton XT IEC large contactor

Catalog Number
DILM32-10(24V60HZ)

EAN
4015082772512

Product Length/Depth
1.8 in

Product Height
3.3 in

Product Width
3.8 in

Product Weight
0.92 lb

Warranty
1 year

Compliances
RoHS Compliant
CE Marked

Certifications
IEC 60947
UL Listed
CSA Certified
EN 60947

Catalog Notes
Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Amperage Rating

32A

HP rating - max

2, 5/ 10, 10, 20, 25 (1/3PH @120,240/208,240,480,600 V)

Number Of Poles

Three-pole

Type

Full voltage non-reversing miniature contactor

Frequency rating

60 Hz

Frame size

45 mm

Terminals

Screw terminals

Coil

24 Vac 60 Hz

Coil voltage

24 Vac, 60 Hz

Contact configuration

1 NO

Continuous ampere rating

32 A

Series

XT IEC

Operation

Non-reversing

Power consumption

15 kW

Resources

Multimedia

S1. E4. Ask the Experts - NEMA, IEC and DP contactors

Contactors Explained

Specifications and datasheets

Global Data Sheet - DILM32-10(24V60HZ)

Eaton Specification Sheet - DILM32-10(24V60HZ)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia