


Model Number

NBB2-8GM25-E3-V3

Features

- **Basic series**
- **2 mm embeddable**
- **Increased operating distance**

Connection



Pinout



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)

Accessories

V3-WM
Female connector, M8, 3-pin, field attachable

BF 8
Mounting flange, 8 mm


V3-GM-2M-PUR
Cable socket, M8, 3-pin, PUR cable

V3-GM
Female connector, M8, 3-pin, field attachable

V3-WM-2M-PUR
Cable socket, M8, 3-pin, PUR cable

EXG-08
Quick mounting bracket with dead stop

Dimensions



Technical Data

General specifications		
Switching element function		PNP NC
Rated operating distance	s_n	2 mm
Installation		embeddable
Output polarity		DC
Assured operating distance	s_a	0 ... 1.62 mm
Reduction factor r_{Al}		0.45
Reduction factor r_{Cu}		0.4
Reduction factor r_{303}		0.75
Nominal ratings		
Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 3000 Hz
Reverse polarity protected		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 100 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.1 µA at 25 °C
No-load supply current	I_0	≤ 15 mA
Indication of the switching state		Multihole-LED, yellow
Functional safety related parameters		
$MTTF_d$		2750 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		Device connector M8 x 1 , 3-pin
Housing material		brass, nickel-plated
Sensing face		LCP
Protection degree		IP67
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Products with a maximum operating voltage of ≤36 V do not bear a CCC marking because they do not require approval.

Release date: 2011-07-07 14:18 Date of issue: 2011-07-07 108368_eng.xml

Copyright Pepperl+Fuchs