


Model Number

NBN25-30GM50-E0

Features

- **Basic series**
- **25 mm not embeddable**
- **Increased operating distance**


Connection



Accessories

BF 30
Mounting flange, 30 mm

Dimensions



Technical Data

General specifications		
Switching element function		NPN NO
Rated operating distance	s_n	25 mm
Installation		not embeddable
Output polarity		DC
Assured operating distance	s_a	0 ... 20.25 mm
Reduction factor r_{Al}		0.5
Reduction factor r_{Cu}		0.4
Reduction factor r_{303}		0.8
Nominal ratings		
Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 200 Hz
Hysteresis	H	typ. 5%
Reverse polarity protected		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 200 mA
Off-state current	I_r	≤ 10 µA
No-load supply current	I_0	≤ 10 mA
Indication of the switching state		all direction LED, yellow
Functional safety related parameters		
$MTTF_d$		1140 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cable PVC , 2 m
Core cross-section		0.34 mm^2
Housing material		brass, nickel-plated
Sensing face		PBT
Protection degree		IP67
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Products with a maximum operating voltage of ≤36 V do not bear a CCC marking because they do not require approval.

Release date: 2011-07-14 10:58 Date of issue: 2011-07-14 088244_eng.xml

Copyright Pepperl+Fuchs