


Model Number

NBN8-18GK50-E0

Features

- **8 mm not embeddable**
- **With increased sealing, protection class IP68 / IP69k**


Connection



Accessories

BF 18
Mounting flange, 18 mm

Dimensions



Technical Data

General specifications		
Switching element function		NPN NO
Rated operating distance	s_n	8 mm
Installation		not embeddable
Assured operating distance	s_a	0 ... 6.48 mm
Reduction factor r_{Al}		0.5
Reduction factor r_{Cu}		0.4
Reduction factor r_{304}		0.7
Nominal ratings		
Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 500 Hz
Reverse polarity protected		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 200 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.1 µA at 25 °C
No-load supply current	I_0	≤ 15 mA
Indication of the switching state		LED, yellow
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cable PVC , 2 m
Core cross-section		0.34 mm^2
Housing material		PBT
Sensing face		PBT
Protection degree		IP68 / IP69K
Note		use only delivered nuts
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Products with a maximum operating voltage of ≤36 V do not bear a CCC marking because they do not require approval.

Release date: 2011-07-14 10:53 Date of issue: 2012-02-03 086349_eng.xml

Copyright Pepperl+Fuchs