

Model Number

NJ40-FP-SN-P4


Features


- **40 mm non-flush**

Technical Data


General specifications		
Switching function		Normally closed (NC)
Output type		NAMUR with safety function
Rated operating distance	s_n	40 mm
Installation		non-flush
Assured operating distance	s_a	0 ... 32.4 mm
Reduction factor r_{Al}		0.4
Reduction factor r_{Cu}		0.3
Reduction factor r_{304}		0.85
Output type		2-wire
Nominal ratings		
Nominal voltage	U_o	8.2 V (R_i approx. 1 kΩ)
Switching frequency	f	0 ... 100 Hz
Current consumption		
Measuring plate not detected		≥ 3 mA
Measuring plate detected		≤ 1 mA
Functional safety related parameters		
$MTTF_d$		7560 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Ambient conditions		
Ambient temperature		-40 ... 100 °C (-40 ... 212 °F)
Mechanical specifications		
Connection type		1/2 NPT terminal compartment, wire cross-section ≤ 2.5 mm²
Core cross-section		up to 2.5 mm²
Housing material		PBT/metal
Sensing face		PBT
Degree of protection		IP68
General information		
Use in the hazardous area		see instruction manuals
Compliance with standards and directives		
Standard conformity		
NAMUR		EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards		EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012
Approvals and certificates		
EAC conformity		TR CU 012/2011
FM approval		
Control drawing		116-0165
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤36 V

Dimensions





Electrical Connection



Release date: 2018-04-19 08:21 Date of issue: 2018-04-19 197958_eng.xml

Data for application in connection with hazardous areas		
Equipment protection level		Gb , Da , Mb
Equipment protection level Gb		
Type of protection		intrinsic safety
CE marking		CE 0102
Certificates		
Appropriate type		NJ 40-FP-SN...
ATEX certificate		PTB 00 ATEX 2049 X
ATEX marking		Ex II 2G Ex ia IIC T6…T1 Gb
Standards		EN 60079-0:2012+A11:2013 , EN 60079-11:2012
IECEx certificate		IECEx PTB 11.0092X
IECEx marking		Ex ia IIC T6...T1 Gb
Standards		IEC 60079-0:2011 , IEC 60079-11:2011
Effective internal inductivity	C_i	≤ 370 nF A cable length of 10 m is considered.
Effective internal inductance	L_i	≤ 300 µH A cable length of 10 m is considered.
Maximum permissible ambient temperature T_{amb}		Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at U_i = 16 V , I_i = 25 mA , P_i = 34 mW , T6 : 73 °C (163.4 °F) T5 : 88 °C (190.4 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at U_i = 16 V , I_i = 25 mA , P_i = 64 mW , T6 : 66 °C (150.8 °F) T5 : 81 °C (177.8 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at U_i = 16 V , I_i = 52 mA , P_i = 169 mW , T6 : 45 °C (113 °F) T5 : 60 °C (140 °F) T4 : 89 °C (192.2 °F) T3 : 89 °C (192.2 °F) T2 : 89 °C (192.2 °F) T1 : 89 °C (192.2 °F) at U_i = 16 V , I_i = 76 mA , P_i = 242 mW , T6 : 30 °C (86 °F) T5 : 45 °C (113 °F) T4 : 74 °C (165.2 °F) T3 : 74 °C (165.2 °F) T2 : 74 °C (165.2 °F) T1 : 74 °C (165.2 °F)
Equipment protection level Da		
Type of protection		intrinsic safety
CE marking		CE 0102
Certificates		
Appropriate type		NJ 40-FP-SN...
ATEX certificate		PTB 00 ATEX 2049 X
ATEX marking		Ex II 1D Ex ia IIIC T135°C Da
Standards		EN 60079-0:2012+A11:2013 , EN 60079-11:2012
IECEx certificate		IECEx PTB 11.0092X
IECEx marking		Ex ia IIIC T135°C Da
Standards		IEC 60079-0:2011 , IEC 60079-11:2011
Effective internal inductivity	C_i	≤ 370 nF A cable length of 10 m is considered.
Effective internal inductance	L_i	≤ 300 µH A cable length of 10 m is considered.
Maximum permissible ambient temperature T_{amb}		Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at U_i = 16 V , I_i = 25 mA , P_i = 34 mW : 100 °C (212 °F) at U_i = 16 V , I_i = 25 mA , P_i = 64 mW : 100 °C (212 °F) at U_i = 16 V , I_i = 52 mA , P_i = 169 mW : 89 °C (192.2 °F) at U_i = 16 V , I_i = 76 mA , P_i = 242 mW : 74 °C (165.2 °F)
Equipment protection level Mb		
Type of protection		intrinsic safety
Certificates		
Appropriate type		NJ 40-FP-SN...
IECEx certificate		IECEx PTB 11.0092X
IECEx marking		Ex ia I Mb
Standards		IEC 60079-0:2011 , IEC 60079-11:2011
Effective internal inductivity	C_i	≤ 370 nF A cable length of 10 m is considered.
Effective internal inductance	L_i	≤ 300 µH A cable length of 10 m is considered.

Release date: 2018-04-19 08:21 Date of issue: 2018-04-19 197958_eng.xml

Maximum permissible ambient temperature T_{amb}	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at U_i = 16 V , I_i = 25 mA , P_i = 34 mW : 100 °C (212 °F) at U_i = 16 V , I_i = 25 mA , P_i = 64 mW : 100 °C (212 °F) at U_i = 16 V , I_i = 52 mA , P_i = 169 mW : 89 °C (192.2 °F) at U_i = 16 V , I_i = 76 mA , P_i = 242 mW : 74 °C (165.2 °F)

Release date: 2018-04-19 08:21 Date of issue: 2018-04-19 197958_eng.xml