Лист тех. данных 3VT9216-6BC00

ETU VT250, 4-pole, line protection ETU DPN, LI IR=63...160A, overload protection IRM=4...8kA short-circuit protection, neutral conductor protection IRN=0.5 to 1xIR screw terminal connections in scope of delivery of switching unit



версия	
торговая марка изделия	SENTRON
наименование изделия	Расцепитель максимального тока (ETU)
исполнение изделия	ETU DPN, LI IR = 63–160 A
Механическая конструкция	
масса нетто	274 g

General Product Approval	Declaration of Conformity	Test Certificates	other
Confirmation		Special Test Certific-ate	Miscellaneous

other

Confirmation

Дополнительная информация

Информация об упаковке
Информация об упаковке
Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3VT9216-6BC00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/ru/ps/3VT9216-6BC00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VT9216-6BC00
CAx-Online-Generator
http://www.siemens.com/cax
Tender specifications
http://www.siemens.com/specifications

© Copyright Siemens

© Copyright Siemens

© Copyright Siemens