SIEMENS

Data sheet 6DL1193-6GA00-0NN0



Figure similar

SIMATIC ET 200SP HA, carrier module 2-fold carrier for holding 2 I/O modules of the ET 200SP HA

General information	
Product type designation	Carrier module 2 times
Product function	
● I&M data	Yes; Asset data
Hardware configuration	
Formation of potential groups	
● support of potential groups	Yes
Slots	
● Number of slots	2
Potential separation	
between backplane bus and supply voltage	Yes; 4 200 V DC/1 min, type test
between the potential groups	Yes; 3 510 V AC/ 5 s, type test (between the power supply groups; due to isolating distance (increased isolation) for future ÜK-III requirement of F technology)
Isolation	
Isolation tested with	1 500 V DC/1 min, type test (between backplane bus and functional ground)
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Dimensions	
Width	52.5 mm; 45 mm when installed
Height	203 mm
Depth	79 mm
Weights	
Weight, approx.	111 g
Classifications	

	Version	Classification
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07

Subject to change without notice
© Copyright Siemens

ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval

EG-Konf. | Miscellaneous | UKCA | China RoHS | UL | KC

General Product Approval

RCM | EAC | IECEx | Declaration of Conformity | CCC | UL

For use in hazardous locations

ATEX | IECEx | Miscellaneous

Maritime application

ABS | Bureau Veritas | DNV

Maritime application

Lloyd's Register LRS | NK / Nippon Kaiji Kyokai | RINA | CCS (China Classification Society)

last modified: 10/23/2025

Subject to change without notice
© Copyright Siemens