SIEMENS

## Data sheet 6ES7223-1BL32-0XB0



SIMATIC S7-1200, Digital I/O SM 1223, 16 DI/16 DO, 16 DI 24 V DC, Sink/Source, 16 DO, transistor 0.5 A

| | |
|---|---|
| **General information** | |
| Product type designation | SM 1223, DI 16x24 V DC, DQ 16x24 V DC |
| **Supply voltage** | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| **Input current** | |
| from backplane bus 5 V DC, max. | 185 mA |
| Digital inputs | |
| ● from load voltage L+ (without load), max. | 4 mA; per channel |
| **output voltage / header** | |
| supply voltage of the transmitters / header | |
| ● present | Yes |
| **Power loss** | |
| Power loss, typ. | 4.5 W |
| **Digital inputs** | |
| Number of digital inputs | 16 |
| ● in groups of | 2 |
| Input characteristic curve in accordance with IEC 61131, type 1 | Yes |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 40 °C, max. | 16 |
| horizontal installation | |
| — up to 40 °C, max. | 16 |
| — up to 50 °C, max. | 16 |
| vertical installation | |
| — up to 40 °C, max. | 16 |
| Input voltage | |
| ● Type of input voltage | DC |
| ● Rated value (DC) | 24 V |
| ● for signal "0" | 5 V DC at 1 mA |
| ● for signal "1" | 15 V DC at 2.5 mA |
| Input current | |
| ● for signal "0", max. (permissible quiescent current) | 1 mA |
| ● for signal "1", min. | 2.5 mA |
| ● for signal "1", typ. | 4 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| for interrupt inputs | |
| — parameterizable | Yes |
| Cable length | |
| ● shielded, max. | 500 m |
| ● unshielded, max. | 300 m |
| **Digital outputs** | |
| Number of digital outputs | 16 |
| ● in groups of | 1 |
| Short-circuit protection | No; to be provided externally |
| Limitation of inductive shutdown voltage to | L+ (-48 V) |
| Switching capacity of the outputs | |
| ● with resistive load, max. | 0.5 A |
| ● on lamp load, max. | 5 W |
| Output voltage | |
| ● Rated value (DC) | 24 V |
| ● for signal "0", max. | 0.1 V; with 10 kOhm load |
| ● for signal "1", min. | 20 V DC |
| Output current | |
| ● for signal "1" rated value | 0.5 A |
| ● for signal "1" permissible range, max. | 0.5 A |
| ● for signal "0" residual current, max. | 10 µA |
| Output delay with resistive load | |
| ● "0" to "1", max. | 50 µs |
| ● "1" to "0", max. | 200 µs |
| Total current of the outputs (per group) | |
| horizontal installation | |
| — up to 50 °C, max. | 8 A; Current per mass |
| Relay outputs | |
| Switching capacity of contacts | |
| — with inductive load, max. | 0.5 A |
| — on lamp load, max. | 5 W |
| — with resistive load, max. | 0.5 A |
| Cable length | |
| ● shielded, max. | 500 m |
| ● unshielded, max. | 150 m |
| **Interrupts/diagnostics/status information** | |
| Alarms | |
| ● Diagnostic alarm | Yes |
| Diagnostics indication LED | |
| ● for status of the inputs | Yes |
| ● for status of the outputs | Yes |
| **Potential separation** | |
| Potential separation digital inputs | |
| ● between the channels, in groups of | 2 |
| Potential separation digital outputs | |
| ● between the channels, in groups of | 1 |
| ● between the channels and backplane bus | 500 V AC |
| **Degree and class of protection** | |
| IP degree of protection | IP20 |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| CSA approval | Yes |
| UL approval | Yes |
| cULus | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| Marine approval | Yes |
| **Ambient conditions** | |
| Free fall | |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● Fall height, max. | 0.3 m; five times, in product package |
| Ambient temperature during operation | |
| ● min. | -20 °C |
| ● max. | 60 °C |
| ● horizontal installation, min. | -20 °C |
| ● horizontal installation, max. | 60 °C |
| ● vertical installation, min. | -20 °C |
| ● vertical installation, max. | 50 °C |
| ● permissible temperature change | 5°C to 55°C, 3°C / minute |
| Ambient temperature during storage/transportation | |
| ● min. | -40 °C |
| ● max. | 70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
| ● Storage/transport, min. | 660 hPa |
| ● Storage/transport, max. | 1 080 hPa |
| Relative humidity | |
| ● Operation at 25 °C without condensation, max. | 95 % |
| **connection method** | |
| required front connector | Yes |
| **Mechanics/material** | |
| Enclosure material (front) | |
| ● Plastic | Yes |
| **Dimensions** | |
| Width | 70 mm |
| Height | 100 mm |
| Depth | 75 mm |
| **Weights** | |
| Weight, approx. | 310 g |

**last modified:** 3/12/2024


Subject to change without notice
© Copyright Siemens