SIEMENS

Лист тех. данных 6ES7361-3CA01-0AA0



Рисунок аналогичен

spare part SIMATIC S7-300, connection IM 361 in expansion rack for connection to central rack (IM360), supply voltage 24 V DC, with C-bus

Напряжение питания	
Номинальное значение (пост. ток)	
● 24 В пост. тока	Да
Входной ток	
из источника напряжения питания L+, макс.	500 mA
Рассеиваемая мощность	
Нормальная рассеиваемая мощность	5 W
Конфигурация аппаратного обеспечения	
Макс. число подключений на ЦП	3
Размеры	
Ширина	80 mm
Высота	125 mm
Глубина	120 mm
Массы	
Масса, прибл.	505 g
Классификации	

	Версия	Классификация
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Разрешения / Сертификаты	
General Product Approval	

© Copyright Siemens

Manufacturer Declaration

General Product Approval	EMV	For use in hazardous locations
Manufacturer Declaration	RCM	ATEX, FM, UL, IECEx

For use in hazardous locations			Maritime application		
ATEX	Miscellaneous	CCC-Ex	ABS	BUREAU VERITAS	DNV

Maritime application				
LRS	NK / Nippon Kaiji Kyokai	PRS	RINA	CCS (China Classification Society)

последнее изменение: 07.04.2025

. © Copyright Siemens