SIEMENS

Лист тех. данных 6ES7365-0BA01-0AA0



Рисунок аналогичен

spare part SIMATIC S7-300, connection IM 365 for connection of an extension rack, without communications bus, 2 modules+ connecting cable 1 m

Входной ток	
из шины на задней стойке 5 В пост. тока, макс.	100 mA
Рассеиваемая мощность	
Нормальная рассеиваемая мощность	0,5 W
Конфигурация аппаратного обеспечения	
Макс. число подключений на ЦП	1; 1 пара
Размеры	
Ширина	40 mm
Высота	125 mm
Глубина	120 mm
Массы	
Масса, прибл.	580 g

Классификации

	Версия	Классификация
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Разрешения / Сертификаты

General Product Approval

Manufacturer Declaration

EG-Konf. UL RCM

© Copyright Siemens

General Product Approval	EMV	For use in hazardous locations			
Manufacturer Declaration	RCM	ATEX	FM	UL	IECEx

For use in hazardous locations			Maritime application		
ATEX	Miscellaneous	CCC-Ex	ABS	BUREAU VERITAS	DNV

Maritime application				
LRS	NK / Nippon Kaiji Kyokai	PRS	RINA	CCS (China Classification Society)

последнее изменение: 07.04.2025

. © Copyright Siemens