SIEMENS

Лист тех. данных 6ES7400-1TA01-0AA0

SIMATIC S7-400, rack UR1, central and distributed with 18 slots, 2 redundant PS can be plugged in



Общая информация	
Обозначение типа продукта	UR1
Конфигурация аппаратного обеспечения	
Монтажные стойки	
● K-шина	Да
● P-шина	Да
Гнезда	
● Число гнезд	18
Стандарты, допуски, сертификаты	
Маркировка CE	Да
маркировка UKCA	Да
Допуск UL	Да
Допуск FM	Да
RCM (ранее C-TICK)	Да
Допуск KC	Да
EAC (ранее ГОСТ-Р)	Да
CCC	Да
Окружающие условия	
Температура окружающей среды при эксплуатации	
● мин.	0 °C
● макс.	60 °C
Температура окружающей среды при хранении/транспортировке	
● мин.	0 °C
● макс.	70 °C
Размеры	
Ширина	482,5 mm
Высота	290 mm
Глубина	27,5 mm
Массы	
Масса, прибл.	4,1 kg
Классификации	

	Версия	Классификация
eClass	16	27-24-22-03
eClass	14	27-24-22-03
eClass	12	27-24-22-03
eClass	9.1	27-24-22-03
eClass	9	27-24-22-03

© Copyright Siemens

eClass	8	27-24-22-03
eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Разрешения / Сертификаты

General Product Approval

Manufacturer Declaration

Miscellaneous

General Product Approval

China RoHS

Miscellaneous

Manufacturer Declaration

EMV

For use in hazardous locations

Declaration of Conformity

FM

For use in hazardous locations

Type Examination Certificate

Maritime application

Maritime application

NK / Nippon Kaiji Kyokai

CCS (China Classification Society)

Environment

последнее изменение: 07.06.2025

© Copyright Siemens