SIEMENS

Лист тех. данных 6ES7460-0AA01-0AB0



Рисунок аналогичен

SIMATIC S7-400, interface module Send IM 460-0 for central coupling without PS transfer, with C-bus

Входной ток	
из шины на задней стойке 5 В пост. тока, макс.	140 mA
Рассеиваемая мощность	
Макс. рассеиваемая мощность	700 mW
Конфигурация аппаратного обеспечения	
Макс. длина линий от первого до последнего подключения	5 m
Техника соединений	
оконечный штекер	6ES7461-0AA0-7AA0
Размеры	
Ширина	25 mm
Высота	290 mm
Глубина	280 mm
Массы	
Масса, прибл.	600 g
Классификации	

	Версия	Классификация
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Разрешения / Сертификаты	
General Product Approval	

© Copyright Siemens

Miscellaneous

General Product Approval			EMV		For use in hazardous locations
China RoHS	Miscellaneous	Manufacturer Declaration			

For use in hazardous locations

	FM		Type Examination Certificate	

Maritime application

				NK / Nippon Kaiji Kyokai	

Maritime application

		CCS (China Classification Society)

последнее изменение: 07.06.2025

. © Copyright Siemens