SIEMENS

Лист тех. данных 6ES7460-3AA01-0AB0



Рисунок аналогичен

SIMATIC S7-400, interface module Send IM 460-3 for distributed coupling up to 102 m, with C-bus

Входной ток	
из шины на задней стойке 5 В пост. тока, макс.	1 550 mA
Рассеиваемая мощность	
Макс. рассеиваемая мощность	7 750 mW
Конфигурация аппаратного обеспечения	
Макс. длина линий от первого до последнего подключения	102,25 m
Техника соединений	
оконечный штекер	6ES7461-3AA0-7AA0
Размеры	
Ширина	25 mm
Высота	290 mm
Глубина	280 mm
Массы	
Масса, прибл.	630 g
Классификации	

	Версия	Классификация
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Разрешения / Сертификаты	
General Product Approval	

© Copyright Siemens

EG-Konf.	UKCA	Miscellaneous	UL	KC	RCM

General Product Approval			EMV		For use in hazardous locations
China RoHS	Miscellaneous	Manufacturer Declaration	RCM	RCM	ATEX

For use in hazardous locations					
IECEx	FM	CCC	IECEx	ATEX	Type Examination Certificate

Maritime application					
ABS	BUREAU VERITAS	DNV	LRS	NK / Nippon Kaiji Kyokai	PRS

Maritime application		
RINA	RMRS	CCS (China Classification Society)

последнее изменение: 07.06.2025

. © Copyright Siemens