SIEMENS

Лист тех. данных 6ES7461-1BA01-0AA0



SIMATIC S7-400, interface module receiver IM 461-1 for central coupling with PS transfer, without C bus,

Входной ток	
из шины на задней стойке 5 В пост. тока, макс.	120 mA
Рассеиваемая мощность	
Макс. рассеиваемая мощность	600 mW
Конфигурация аппаратного обеспечения	
Макс. длина линий от первого до последнего подключения	1,5 m
Размеры	
Ширина	25 mm
Высота	290 mm
Глубина	280 mm
Массы	
Масса, прибл.	610 g

Классификации

	Версия	Классификация
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Разрешения / Сертификаты

General Product Approval

Miscellaneous

© Copyright Siemens

General Product Approval			EMV		For use in hazardous locations
China RoHS	Miscellaneous	Manufacturer Declaration	RCM	RCM	IECEx

For use in hazardous locations					
ATEX	FM	CCC	IECEx	Type Examination Certificate	ATEX

Maritime application					
ABS	BUREAU VERITAS	DNV	LRS	NK / Nippon Kaiji Kyokai	PRS

Maritime application		
RINA	RMRS	CCS (China Classification Society)

последнее изменение: 07.06.2025

. © Copyright Siemens