SIEMENS

Data sheet 6ES7972-0BA70-0XA0

product type designation	**PROFIBUS connector**
product description	PROFIBUS bus connector, RS 485, Fast Connect, without programming port, 90°

SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, 15.8x 72.2x 36.4 mm (WxHxD), Insulation displacement method FastConnect, without PG socket



suitability for use	For connecting PROFIBUS stations to the PROFIBUS bus cable
transfer rate	
transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of electrical connections	
● for PROFIBUS cables	2
● for network components or terminal equipment	1
type of electrical connection	
● for PROFIBUS cables	Integrated insulation displacement contacts for 2-core PB FC installation cables
● for network components or terminal equipment	9-pin sub D connector
type of electrical connection / FastConnect	Yes
mechanical data	
design of terminating resistor	Resistor combination integrated and connectable via slide switch. Isolation function: When resistor is connected, outgoing bus is disconnected
material / of the enclosure	plastic
locking mechanism design	Screwed joint
design, dimensions and weights	
type of cable outlet	90 degree cable outlet
width	15.8 mm
height	72 mm
depth	36.4 mm
net weight	34 g
ambient conditions	
ambient temperature	
● during operation	-25 ... +60 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
protection class IP	IP20
product features, product functions, product components / general	
product feature	
● silicon-free	Yes
product component	
● PG connection socket	No
● strain relief	Yes
standards, specifications, approvals	
certificate of suitability	
● RoHS conformity	Yes
● UL approval	Yes

Subject to change without notice
© Copyright Siemens

reference code	
● according to IEC 81346-2	XG
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP

last modified: 8/16/2023

Subject to change without notice
© Copyright Siemens